

NK-PDAF

The NK models incorporate such features as a ready brew light for optimum brewing temperature, independent hot water faucet, and back-up pour in feature. We have added a branding box that offers an updated style hiding the switches from the end user, while providing a sleek cover with the option of your company's logo and artwork to capture your coffee audience. Switches are viewable with a simple flip, and giving the operator brewing instructions at a glance. Private labeling is now offered with Newco's State of the Art Branding capabilities.



NK-PDAF



Made in the USA

STYLE: *Automatic*

BREW OPERATIONS: *Analog / Digital timer*

HEATING SYSTEM: *Tank Reservoir*

WATER DELIVERY: *Displacement*

TANK SYSTEM: *Closed*

VOLTAGE: *120V or 120V/240V Only*

CABINET: *Semi-Modular*

FLOW REGULATION: *Flow Washer*

BACKUP POUR IN: *Yes*

FAUCET: *Coil / Pressurized*

Low Profile Design:

Allows unit to be easily placed with out modifications to locations. Fits under low cabinet construction.

Ready Light:

Provides visual notification to user as to when brewer is at optimum temperature in which to brew.

Back-up pour-over:

Allows the account to continue to have fresh brewed coffee even if an interruption in the automation of the machine or water line should occur.

Detachable Base:

Detachable base allow thermal models to be converted to brew into a variety of thermal bases.

Item #	Model	H	W	D	Ship Wt.	Volts	Watts	Amps	Volts	Watts	Amps
705326	NK-PDAF	26.0	11	17.75	44	120	1400	14.6	120	1100	12.3