

BROOK

P.O.U. Water Coolers



igo PRODUCTS

Global Trade Works LLC

For those needing a long-term use Point-Of-Use (POU) system, Brook is the ideal model. Its sleek one-piece blow-molded cabinet is made of high-density polyethylene and incorporates UV resistance additives, making it a must-have for your rental fleet.

- ☑ Elegant and unique look
- ☑ Food grade stainless steel water ways
- ☑ Large and durable drip tray
- ☑ UV resistance
- ☑ High quality components
- ☑ 2 years Limited Warranty



POWERED BY INNOVATION



Waterways is the premier cooler manufacturer in the industry, with a long legacy of high quality and design. The Brook is a continuation of our dedication to innovation.

NEWCO 
newcocooffee.com

800.325.7867 • 3650 New Town Blvd. • St. Charles, MO 63301

TECHNICAL DATA & SPECIFICATION

BROOK

P.O.U. Water Coolers

Cabinet & Chassis:

One-piece blow molded high-density polyethylene plastic that resists cracking, fading, and discoloration. Designed to hide scrapes and scratches caused by rough usage.

Cold Water Refrigeration Unit:

Convection cooled condenser with internal spring mounted, hermetically sealed compressor and an automatic overload protector. No lubrication needed.

Cold Water Reservoir:

Food grade stainless steel (SUS304), 0.85-gallon (3.2 liter) reservoir provides superior chilling for great tasting water. Highly polished surface is easy to clean and maintain.

Hot Water Tank:

Food grade stainless steel (SUS304), 0.26-gallon (1.0 liter) capacity. The 375-watt heating element ensures precise temperature control. Removable thermostat and heating element allow for easy service.

Cooler Dimension

Height	46.2 in (1173mm)
Width	13.9 in (353mm)
Depth	14.1 in (357mm)

Cooler Weights

Hot & Cold	36.4 lb (16.5kg)
------------	------------------

Shipping Dimension

Height	48.7 in (1238mm)
Width	15.8 in (400mm)
Depth	16.3 in (415mm)

Shipping Weights

Hot & Cold	38.6 lb (17.5kg)
------------	------------------

Container Loading Quantity

20° FCL	70 Units
40° FCL	300 Units

Electrical

115 volts (60 Hertz) or 220 volts (50 Hertz)

Refrigerant

All unit contain HFC-134a refrigerant

The unique Brook cooler design offers a streamlined look and durable protection. The HDPE blow mold cabinet can be easily removed for refurbishing and service access.

Specifications are subject to change without notice. Filter System not included with cooler.



Electronic Dispensing



Mechanic Dispensing



Filters Installation