NK-PPAF





The NK models incorporate such features as a ready brew light for optimum brewing temperature, independent hot water faucet, and back-up pour in feature. We have added a branding box that offers an updated style hiding the switches from the end user, while providing a sleek cover with the option of your company's logo and artwork to capture your coffee audience. Switches are viewable with a simple flip, and giving the operator brewing instructions at a glance. Private labeling is now offered with Newco's State of the Art Branding capabilities.





Low Profile Design:

Allows unit to be easily placed with out modifications to locations. Fits under low cabinet construction.

Ready Light:

Provides visual notification to user as to when brewer is at optimum temperature in which to brew.

Back-up pour-over:

Allows the account to continue to have fresh brewed coffee even if an interruption in the automation of the machine or water line should occur.

Detachable Base:

Detachable base allow thermal models to be converted to brew into a variety of thermal bases.

Style: Automatic Brew Operations: Analog / Digital timer Heating System: Tank Reservoir Water Delivery: Displacement Tank System: Closed Voltage: 120v or 120v/240v Only Cabinet: Semi-Modular Flow Regulation: Flow Washer Back up Pour in: Yes Faucet: Coil / Pressurized

Additional Information

Part Number	Model	Height	Width	Depth	Ship Wt.	Volts	Watts	Amps
PN: 705118	NK-PPAF	22.2	9.5	18	42	120V	1400W	14.6A
					Canadian Electrical 120V		1100W	12.3A



