STREAM

P.O.U. Water Coolers



The sleek and sophisticated design of the Stream Point-Of-Use (POU) system features variable hot and

cold temperature controls and large LED display with a touch screen. This model is reliable, efficient and an attractive system for any home or office space.

- ☑ Variable hot and cold temperature controls

- ☑ Large and durable drip tray
- ☑ 2 years Limited Warranty











Waterways is the premier cooler manufacturer in the industry, with a long legacy of high quality and design. The Stream is a continuation of our dedication to innovation.

30021 Tomas Street, Suite 300 | Rancho Santa Margarita, CA 92688, USA
Tel: 1-909-230-4753 | www.thewaterwayscompany.com

TECHNICAL DATA & SPECIFICATION

STREAM

P.O.U. Water Coolers

Cabinet & Chassis:

Sleek and sophisticated cooler design built with ABS plastic front panels and metal side panels for durability.

Cold Water Refrigeration Unit:

Convection cooled condenser that is spring mounted and hermetically sealed with automatic overload protector. No lubrication needed.

Cold Water Reservoir:

The food grade stainless steel type SUS304, 0.95-gallon (3.6 liter) reservoir provides superior chilling for great tasting water and the polished surface makes for easy cleaning and maintenance.

Hot Water Tank:

The 520-watt heating element ensures precise temperature control while the removable thermostat and heating element make for easy service. The food grade stainless steel type SUS304, comes with a 0.32-gallon (1.2 liter) capacity.

In the case of a water leak, the detector will give warning signal shown on LED display.





Cooler Dimensions	
Height	46.7 in (1185mm)
Width	12.6 in (320mm)
Depth	15.3in (388mm)
Faucet to Top	10.8 in (274mm)

Faucet to Drip Tray 10.3 in (261mm)

Cooler Weights

Hot & Cold 44.1 lb (20.0kg)

Shipping Dimensions

Height	49.8 in (1264mm)
Width	15.2in (387mm)
Depth	17.7 in (450mm)

Shipping Weights

Hot & Cold 46.3lb (21.0kg)

Container Loading Quantity

20° FCL	70 Units
40° FCL	290 Units

Electrical

115 volts (60 Hertz) or 220 volts (50 Hertz)

Refrigerant

All unit contain HFC-134a refrigerant

The open door cabinet allows for ease of filter changes and has a roomy compartment for four inline filter cartridges, booster pump, and solenoid valves.

Specifications are subject to change without notice. Filter System not included with cooler.



Electronic Dispensing

