

# COMMERCIAL BARISTA

CB



CB shown with 2.5 Liter Zojirushi Server

Cafe Barista brewing technology controls the three vital aspects of the coffee brewing recipe: water temperature, water volume, and water contact time - extracting the best cup of coffee possible. Cafe Barista opens up a new world of flavor profile control by allowing you to select two different settings. And you can brew into two different size dispensers and/or two different strengths with the same machine. You control the time, volume and temperature with the touch of a button (no tools needed).

Cafe Barista brewers greatly enhance account profitability by allowing two different beverages to be brewed on a single unit while dramatically reducing installation and set up time.



# CB

**“Brew 1” and “Brew 2”** selectors provide a choice of two adjustable flavor profiles or portion sizes.

**Water Volume:** May be adjusted through the digital display: 30 ounces to 255 ounces.

**Digital Display:** Counts down the minutes and seconds remaining until the basket has finished draining. Visa-Brew time may be adjusted.

**Water Temperature:** May be adjusted between 170 and 210 degrees from the front touch pad.

**Pre-infusion:** Wets the coffee grounds to de-gas fresh roasted coffee in the basket so that the grounds may be evenly saturated during the brew cycle.

**Pulse Brewing:** Pulses your chosen water temperature onto the coffee bed for ultimate taste profile accuracy.

**Service Light:** Indicates the appropriate time for scheduled maintenance and accompanies five “Error” messages when operation is interrupted by a fault.

**Water Filtering Light:** Offers service operators an opportunity to communicate added value to customers by indicating that fresh water is being drawn into the tank through the filtration system.

**Filter Monitor:** Alerts the customer when it is time to change the water filter.

**Audible Signal:** Alerts user when the filter basket has finished draining. Your fresh hot coffee is ready!

**Coffee Monitor Light:** Indicates the freshness of the last beverage brewed.

**Cycle Counter:** Monitors the number of brew cycles.

**Power Conservation:** Allows energy saving during idle time.

**Brewer Height and Electrical Specifications:** 120/240 volt - 1PH - 5500watt - 22.9 amp - needs 4 wire plug and cord (not provided) & 30 amp service.

## Additional Information

Part Number	Model	Height	Width	Depth	Volts	Watts	Amps	Ship Weight
PN: 151370	CB	27.1	9.5	20.75	240	5500	22.9	34